

# Traveling Block

The traveling block has a robust and field-proven design that together with the crown block facilitates hoisting of high loads in the most reliable and efficient way possible.

## Technical Specifications

	TB 500 LR 550	TB 650 LR 700	TB 750 LR 800	TB 1000 LR 1050
Hoisting system lifting capacity	500 shtons (454 mtons)	650 shtons (590 mtons)	750 shtons (680 mtons)	1000 shtons (907 mtons)
Load rating	550 shtons (499 mtons)	700 shtons (635mtons)	800 shtons (726mtons)	1050 shtons (953mtons)
Wire pull ( max)	72 shtons (65 mtons)	72 shtons (65 mtons)	72 shtons (65 mtons)	96 shtons (87.5 mtons)
Drill line diameter	1 1/2" (38mm)	1 1/2" (38mm)	1 1/2" (38mm)	2" (51mm)
Weight	9300 kg (20500lb)	9700 kg ( 21400lb)	1300 kg (28700lb)	17200 kg (37900lb)
Lug capacity	55 shtons (50 mtons)	55 shtons (50 mtons)	55 shtons (50 mtons)	88 shtons (80 mtons)
Sheaves in system	5	6	7	7
Sheave diameter	60 inch (1524 mm)	60 inch (1524 mm)	60 inch (1524 mm)	72 inch (1829 mm)

